

TRAVIA H/T

FEATURES & BENEFITS

- 5 rib tread design for maximizing traction on the road
- Multiple zig-zag sipes provide increased biting edges
- Circumferential grooves enhance water evacuation
- Special shoulder block design improves handling and cornering ability
- Jointless Nylon spiral wrap cap ply for improved uniformity and resistance to heat buildup



PRODUCT CODE	TIRE SIZE	LOAD RANGE	SIDE WALL	UTQG	TREAD DEPTH (32NDS)	SECTION WIDTH (INCH)	OVERALL DIAMETER (INCH)	MAX LOAD SINGLE/DUAL	MAXIMUM PRESSURE (PSI)	WEIGHT (LB)	TREAD CONSTRUCTION
2100	235/75R15 109T	XL	OWL	640 A A	12	9.25	28.86	2271	50	30	2P+2S+1N
2101	265/75R16 116T	SL	OWL	640 A A	12	10.51	31.65	2756	51	38	2P+2S+1N
2102	215/70R16 100H	SL	OWL	640 A A	12	8.70	27.87	1764	51	27	2P+2S+1N
2103	225/70R16 103T	SL	OWL	640 A A	12	8.98	28.43	1929	51	29	2P+2S+1N
2104	235/70R16 106T	SL	OWL	640 A A	12	9.45	28.98	2094	51	30	2P+2S+1N
2105	245/70R16 107T	SL	OWL	640 A A	12	9.76	29.53	2403	51	32	2P+2S+1N
2106	265/70R16 112T	SL	OWL	640 A A	12	10.71	30.63	2469	51	35	2P+2S+1N
2107	265/70R17 115T	SL	OWL	640 A A	12	10.71	31.65	2679	51	37	2P+2S+1N
2108	235/65R17 104T	SL	BSW	640 A A	12	9.45	29.06	1984	51	31	2P+2S+1N
2109	245/65R17 107T	SL	BSW	640 A A	12	9.76	29.53	2149	51	33	2P+2S+1N
2110	265/65R17 112H	SL	OWL	640 A A	12	10.71	30.55	2469	51	---	2P+2S+1N
2111	215/60R17 96H	SL	OWL	640 A A	12	8.70	27.17	1565	51	---	2P+2S+1N
2112	235/60R18 103H	SL	OWL	640 A A	12	9.45	29.09	1929	51	---	2P+2S+1N
2113	215/55R18 95H	SL	OWL	640 A A	12	8.90	27.28	1521	51	---	2P+2S+1N
2185	LT215/75R15 106/103R	D	BSW	---	14.2	8.50	27.68	2095/1930	65	34	2P+2S+1N
2186	LT235/75R15 116/113S	E	BSW	---	14.2	9.25	28.86	2755/2535	80	---	2P+2S+1N
2175	LT31X10.50R15 109R	C	BSW	---	14.2	10.55	30.51	2270	50	0	2P+2S+1N
2176	LT235/85R16 120/116R	E	BSW	---	14.2	9.25	31.73	3042/2778	80	40	2P+2S+1N
2177	LT225/75R16 115/112R	E	BSW	---	14.2	8.78	29.29	2680/2470	80	36	2P+2S+1N
2178	LT245/75R16 120/116R	E	BSW	---	14.2	9.76	30.47	3042/2778	80	40	2P+2S+1N
2179	LT265/75R16 123/120R	E	BSW	---	14.2	10.51	31.65	3415/3085	80	44	2P+2S+1N
2181	LT235/80R17 120/117R	E	BSW	---	14.2	9.25	31.81	3085/2835	80	41	2P+2S+1N
2182	LT245/75R17 121/118R	E	BSW	---	14.2	9.76	31.50	3195/2910	80	41	2P+2S+1N
2187	LT245/70R17 119/116S	E	BSW	---							UNDER DEVELOPMENT
2183	LT265/70R17 121/118R	E	BSW	---	14.2	10.71	31.65	3195/2910	80	45	2P+2S+1N
2184	LT285/70R17 121/118S	D	BSW	---	14.2	11.50	32.76	3195/2910	65	50	2P+2S+1N